

GEOFORM INTERNATIONAL, INC.	DINO SIX
Dimensions Length 18 ft. Width 71 in. Height 64 in. Weight (less fuel) 3,240 lbs.	Slurry Pump Manufacturer Geoform International, Inc. Discharge Diameter 6 in. Performance 1,600 GPM Max 1,100 GPM @ 50 ft. TDH Supplied with open faced trash impeller and enclosed impeller
Working Capacity Working Depth 10 ft. Cut Width 66 in.	Travel System Double pulley hydraulic windlass with 2 hydraulic motors
Floatation 2 (two) pontoons 26 in. X 22 in. X 168 in. Construction Stainless Steel 16 gauge, 3 separate compartments each float (6 compartments total) Internal stiffeners on all sides	Cutterhead Width 66 in. Diameter 14 in. Drive Variable speed duel hydraulic motor Direct Drive Replaceable, hardened steel trencher teeth and mixing paddles
Engine Type Cummins 4 cylinder turbo-charged diesel Horsepower 60 hp @ 2800 rpm Fuel capacity 20 gallons	Hydraulic System Pump Tandem gear 2.60in ³ /rev. and .91in ³ /rev. Filtration 10 micron Reservoir 20 gallons Oil cooler thermostatically controlled Stainless steel tubing on boom Impeller high-low speed selector valve
Instrumentation Tachometer/hour meter Slurry pump hydraulic pressure gauge Cutterhead hydraulic pressure gauge Discharge pressure gauge	Safety Engine Shut-Down High engine coolant temperature Low engine oil pressure High hydraulic oil temperature Low hydraulic oil level

Dealer Representative and Commercial Sales:

David Wentland, P.E.
Docks & Marinas, Inc.
1304 Raebrooke Lane
De Pere, WI 54115-8028
p. 920-621-3464 f. 866-710-0893
davewentland@gmail.com
www.docks-marinas.com